



Specification  
CM55  
AC Clamp Meter



**ELECTRICAL**

All specified accuracies are at 23°C ± 5°C, <80% RH for 1 year.

**Temperature coefficient:** add 0.1 x (specified accuracy) per °C. (0°C to 18°C, 28°C to 40°C).

All accuracies below are expressed as ± (percentage of reading + digits)

**DC Voltage**

Range	Resolution	Input impedance	Accuracy
400V	0.1V	1MΩ	1.0% + 3
600V	1V		

Overload protection: 660V DC or AC rms

**AC Voltage**

Range	Resolution	Input impedance	Accuracy (50 to 400Hz)
400V	0.1V	1MΩ	1.2% + 3
600V	1V		

Overload protection: 660V DC or AC rms



Specification  
CM55  
AC Clamp Meter

**ENVIRONMENTAL**

Temperature & Humidity

(Operating): 0°C to 40°C <80% R.H., non-condensing

(Storage): -10°C to 60°C < 70% R.H., batteries removed

Altitude: up to 2000m

Pollution degree: 2

**SAFETY**

Conforms to BS EN 61010-1, BS EN 61010-2-032, CAT III 600V Class II, double insulation

**EMC**

Conforms to BS EN 61326-1

**SPECIFICATION FOR TL16 TEST LEADS**

Maximum voltage: 1000V AC/DC

Maximum current 10A continuous

Connector: 4mm banana plug with fixed shroud

**Environmental**

Temperature (Operating & Storage): 0°C to 40°C

Altitude: up to 2000m

Pollution degree: 2

**Safety**

Conforms to BS EN 61010-031, CAT IV 600V, CAT III 1000V, 10A (probe tip covers fitted)

CAT II 1000V, 10A (probe tip covers removed)

Class II, double insulation



Specification  
CM55  
AC Clamp Meter

**AC Current**

Range	Resolution	Accuracy	
		(50 to 60Hz)	(60 to 400Hz)
40A	0.01A	1.9% + 3	3.0% + 5
400A	0.1A		

Overload protection: 660A DC or AC rms

**Resistance and Continuity**

Range	Resolution	Open circuit voltage	Accuracy	Audible indication
400 Ω	1Ω	-1.5V dc	1.0% + 2	<25Ω

Overload protection: 600V DC or AC rms

**GENERAL**

Display: 3½ digit liquid crystal display with maximum reading 3999

Sample rate 2 times/sec

Polarity: Automatic, positive implied, '-' for negative polarity indication

Overrange: (OL) is displayed

Power: 2 x 1.5V, AAA alkaline batteries (IEC LR03, NEDA 24A)

Battery life (alkaline): 500 hours typical for ACV and ACA ranges

800 hours typical for DCV and Ω ranges

Low battery indication: symbol is displayed

Auto power off: after 10 minutes

Jaw opening capability: 25.4mm

Dimensions: 203 x 75 x 32mm

Weight: 262g approx, including batteries

Includes: carrying case, set of TL16 test leads, 2 x 1.5V AAA batteries, instructions

**Check out what else you can get from Martindale:**

- 18th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers



Martindale Electric Company Limited  
Metrohm House, Imperial Park, Imperial Way,  
Watford, Hertfordshire, WD24 4PP  
Tel: +44 (0)1923 441717 Fax: +44 (0)1923 446900  
E-mail: sales@martindale-electric.co.uk  
Website: www.martindale-electric.co.uk



© 2015 Martindale Electric Company Ltd.  
Registered in England No. 3387451. Rev1 LITCM55