



MTL10
MTL20 MTL15

CAT IV 600V
CAT IV 1000V

Key features

- Four illuminated bands for 360° AC/DC voltage indication
- Simple and safe with no batteries or ranges
- High intensity long life LEDs
- Interchangeable GS38 probes
- Heavy duty double insulated cable with contrasting inner core to identify damage

Additional features MTL15:

- Extended voltage indication to 690V
- Multiple probes included
- CAT IV 1000V safety rating

Additional features MTL20:

- Twin test buttons eliminate phantom voltages

	MTL10	MTL20	MTL15
Self Powered	✓	✓	✓
AC/DC Voltage Indication	✓	✓	✓
360 Degree Viewing	✓	✓	✓
LED Voltage Thresholds	50/100/200/400V	50/100/200/400V	50/230/400/690V
Low Impedance Function		✓	
Interchangeable probes	3	3	6

John Drummond test lamps have been designed to safely prove dead in all areas including CAT IV supply side applications. High intensity LEDs illuminate 4 distinct bands at different voltage thresholds to provide a 360° viewing angle even in bright sunlight. This allows accurate identification of potentially lethal voltages and distinguishes between 110V, 230V and phase to phase voltages.

The MTL15 has a CAT IV 1000V safety rating making it suitable for use in all installation categories and a higher 690V threshold. The MTL20 has a low impedance mode to safely dissipate phantom voltages.

The test lamps are supplied with interchangeable test probes for safe and easy measurement in all types of application particularly where access is restricted. The right angled probe can be rotated through 90, 180 and 270 degrees and locked in position.

All models comply with the latest standard for voltage indicators, EN61243-3 which prohibits the use of fuses. Additional safety features include finger guards and a two layer double insulated cable with contrasting inner sheath, making it easy to identify cable damage.



Keeping You Safe

Drummond MTL Series Test Lamps

Specifications

FUNCTION	MTL10	MTL20	MTL15
ELECTRICAL			
Maximum working voltage	500V AC rms, 750V DC		1000V AC/DC rms
Nominal voltage threshold indications	50, 120, 230, 400V AC/DC rms		50, 230, 400, 690V AC/DC rms
Nominal voltage threshold tolerance	Conforms to BS EN 61243-3		
Range detection	Automatic		
Response time	<0.1s		
Frequency range	DC, 40-65Hz		
Test current (in)	<3.5mA at 500V AC rms, 750V DC		<3.5mA at 1000V AC/DC rms
Test current (switches operated)	-	approx. 28mA at 230V AC rms, DC approx. 60mA at 500V AC rms, DC	-
Duty ratio	30s ON (operated) / 240s OFF (recovery)		
ENVIRONMENTAL			
Temperature & humidity (operating & storage)	-10°C to 55°C, ≤ 85% R.H.		
Altitude	up to 2000m		
Pollution degree	2		
IP rating	IP64		
GENERAL			
Power	from circuit under test		
Dimensions	213(L) x 112(W) x 72(D) mm		
Weight	320g approx.	350g approx.	320g approx.
SAFETY			
	BS EN 61243-3		
Conforms to	BS EN 61010-1 CAT IV 600V Class II, double insulation		BS EN 61010-1 CAT IV 1000V, Class II, double insulation
	Probe tips comply with GS38		
EMC			
Conforms to	BS EN 61326-1		
Recommended proving unit	440V – PD440 or PD440S		690V – PD690 or PD690S

Included

MTL10: 2 straight prods, 1 L-shaped prod and instruction manual

MTL20: 2 straight prods, 1 L-shaped prod and instruction manual

MTL15: 2 straight prods, 2 long straight prods, 1 long angled prod, 1 L-shaped prod and instruction manual

Related products

MTL10PD 400V test lamp, proving unit & combination carry case

MTL20PD 400V test lamp, proving unit & combination carry case

MTL15PD 690V test lamp, proving unit & combination carry case

Martindale Electric Co. Ltd.

Metrohm House, 12 Imperial Park,

Imperial Way, Watford WD24 4PP.

T: 01923 441717 F: 01923 446900

www.martindale-electric.co.uk

sales@martindale-electric.co.uk

Ver. A2.0

Due to policy of continuous development, Martindale Electric reserves the right to alter equipment specification and description outlined in this document without prior notice. No part of this document shall be deemed to be part of any contract for the equipment unless specifically referred to as an inclusion within such contract. © 2020 Martindale Electric Co. Ltd.