



## Specification

### PC15250 Mk2

### Phase Sequence Indicator



#### Electrical

Input voltage range: 50V to 600V AC (Phase to Phase)

Input frequency: 40 to 60Hz

Input current: < 3mA

#### Environmental

Temperature (Operating & Storage): -10°C to 55°C

Humidity (Operating & Storage): ≤ 85% R.H

Altitude: up to 2000m

Pollution Degree: 2

#### General

Power: from circuit under test

Fuses: 600V 0.5A 50kA HRC rated fuses (6x32mm) x 3, one in each probe

Dimensions: 116(L) x 69(W) x 25(D) mm

Weight packed: 361g approx

Includes: instructions

#### Safety

Conforms to GS38 & BS EN61557-7, CAT IV 600V

Class II, Double Insulation

#### EMC

Conforms to BS EN61326-2-2

Check out what else you can get from Martindale:

- 18th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers



Martindale Electric Company Limited  
Metrohm House, Imperial Park, Imperial Way, Watford, Hertfordshire,  
WD24 4PP Tel: +44(0)1923 441717 Fax: +44 (0)1923 446900

E-mail: [sales@martindale-electric.co.uk](mailto:sales@martindale-electric.co.uk)

Website: [www.martindale-electric.co.uk](http://www.martindale-electric.co.uk)

© 2013 Martindale Electric Company Ltd.  
Registered in England No. 3387451. E. & O.E. Document Rev3 LITPC15250