



Specification
TEK404 Mk2 Continuity Tester



Probe voltage: 2.2V DC

Test current: < 50 microAmp (across short circuit)

Continuity range: 0Ω to 2.2kΩ ± 10%

Audible output level:

85dB minimum at 30 cm with 0Ω continuity resistance

LED indication: Bright orange LED

Buzzer and LED intensity reduce with increasing continuity resistance

Alarm function: Pulsed buzzer and LED indication if unit is connected to live circuit voltage >30V AC or 30 >V DC ± 20V

Compliance: BS EN 61010 - 2001 CAT III 600V overvoltage
Do not use in CAT IV environments

Operating temperature range: -10 to 40°C at max 70% RH

Ingress: IP40 per BS EN 60529 :1991

Power supply: 9V, MN1604/PP3 alkaline battery

Dimensions: 150 x 64 x 31mm

Weight: Approx 290g (including leads & battery)

Supplied with CAT III 600V test leads, insulated croc clips and MN1604 battery.

Beltclip: On rear face

Check out what else you can get from Martindale:

- 18th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers



Martindale Electric Company Limited
Metrohm House, Imperial Park, Imperial Way,
Watford, Hertfordshire, WD24 4PP, UK
Tel: +44(0)1923 441717 Fax: +44 (0)1923 446900
E-mail: sales@martindale-electric.co.uk
Website: www.martindale-electric.co.uk



© Martindale Electric Company Ltd. 2009
Registered in England No. 3387451. Document Rev 2 LIT404