



VT25PD Voltage Indicator & Proving Device Kit

Voltage Indication

VT25



CAT IV
1000V

IMPORTANT: Voltage Indicators should always be tested with a proving unit or known live source before and after use.



Proving Device

PD690



Safe isolation procedures require voltage indicators to be proved against a known source both before and after use. As the UK market leader in voltage indication, Martindale supplies a kit with both the VT25 two pole and matching proving unit, this is all housed in a TC70 carry case with a neck strap, making it easy to carry and use the equipment on site

SPECIFICATION

- Voltage range: 12-690V AC/DC
- Frequency range DC: 16-400Hz
- LED indication: ±12, 24, 50, 120, 230, 400, 690V
- Single Pole Phase Test: 100-690V
- Frequency range DC: 50-60Hz
- Phase Rotation Test: 120-400V
- Frequency range DC: 50-60Hz
- Continuity Range: 0-500kΩ
- GS38 caps: removable
- Standard & Regulations: BS EN 61243-3 2010
- Cable length: 1.2m
- IP rating: IP64
- Auto power off
- Torch light: White LED
- Power: 2 x 1.5V AAA
- Weight: 130g (with batteries)
- Dimensions: 205 x 67 x 27mm
- Includes: battery and manual

The PD690 proving device produces 700V AC/DC to enable voltage indicators and other devices with ranges up to 700V to be checked. It is a portable, battery powered proving unit with the option of being driven from a 12V supply via a car or mains power supply. The kit is supplied with a combination carry case for both VI and PD products.

Suitable for: Drummond Test Lamps, Digital Multimeters, Low Impedance Voltage Testers (LCD display).

SPECIFICATION

- Output voltage: 700V nominal
- Output frequency: 50Hz nominal
- Environmental**
- Operating temperature: -10°C to 40°C at max. 70% R.H.
- Altitude: up to 2000m
- Pollution degree: 2
- General**
- Power: Internal batteries or external power source
- Internal batteries: 6 x 1.5V, AA alkaline batteries (IEC LR6, NEDA 15A)
- External power source: 12V DC max. at 2A min.
- External power socket: 2.5mm jack socket, centre positive
- Dimensions: 143 x 84 x 50mm.
- Weight packed: 400g approx. with batteries
- Includes: 6 x 1.5V AA alkaline batteries, instructions

Due to policy of continuous development, Martindale Electric reserves the right to alter equipment specification and description outlined in this document without prior notice. No part of this document shall be deemed to be part of any contract for the equipment unless specifically referred to as an inclusion within such contract. © Martindale Electric Co. Ltd. 2016

Martindale Electric Company Ltd.

Metrohm House, Imperial Trading Estate, Imperial Way, Watford, WD24 4PP. Tel: 01923 441717 Fax: 01923 446900
E-mail: sales@martindale-electric.co.uk Web site: http://www.martindale-electric.co.uk rev 1