

**Kit includes:**

- DT173 digital thermometer
- TT1P bead thermocouples
- TT6K penetration probe
- TT8K surface probe
- Hard carry case

The Martindale THERMOKITLGN includes the DT173 Thermometer with max function and two thermocouple probes in a soft carry case. The kit can be used for temperature testing and monitoring in accordance with Health & Safety Guidelines to avoid water temperature and conditions that can favour the growth of Legionella and other bacteria. The surface and immersion probes simplify measurement on pipework and tanks.



Keeping You Safe

THERMOKITLGN

Legionella Testing Thermometry Kit

Specifications

DT175 Dual Input Digital Thermometer

Electrical

All specified accuracies are at 23°C ± 5°C, <75% RH for 1 year, not including thermocouple error.

Temperature coefficient: 0.1 x (applicable accuracy) per °C. (0°C to 18°C, 28°C to 50°C)

Temperature scale: Celsius or Fahrenheit, user-selectable

Thermocouple type: K

Measurement range: -200°C to 1372°C. (-328°F to 1999°F)

Note: Measurement range will be limited by the range of the thermocouple probe used.

Resolution: 0.1° to 199.9°C/°F, 1° ≥ 200°C/°F

Temperature accuracy:

Range	Accuracy
-200°C to -60°C	0.1% of rdg + 2°C
-60°C to 1372°C	0.1% of rdg + 1°C
-328°F to -76°F	0.1% of rdg + 4°F
-76°F to 1999°F	0.1% of rdg + 2°F

Input protection: 24V DC or AC rms maximum input voltage on any combination of input pins.

Input connector: Accepts standard miniature thermocouple connectors (flat blades spaced 7.9mm. center to center).

Supplied thermocouple probe:

4-foot Type K thermocouple bead probe (teflon tape insulated).

Maximum insulation temperature 260°C (500°F).

Probe accuracy ± 2.2°C or ± 0.75% of reading (whichever is greater). -50°C to 1300°C. (-58°F to 2000°F).

Note: Measurement range will be limited by the range of the thermocouple probe used.

General

Display: 3½ digit liquid crystal display (LCD) with maximum reading of 1999

Measurement rate: 2.5 times/second

Polarity: Automatic, positive implied, '-' for negative polarity indication

Overrange: (OL) is displayed

Power: 4 x 1.5V, AAA alkaline batteries (IEC LR03, NEDA 24A)

Battery life: 200 hours typical with alkaline batteries

Low battery indication: Low battery symbol is displayed

Auto power off: After minutes

Dimensions: 160 mm (H) x 83 mm (W) x 38 mm (D).

Weight: Approx. 240g, including batteries

Includes: Rubberised holster, Type K bead thermocouple, 4 x 1.5V AAA alkaline batteries and instructions

Environmental

Temperature & Humidity: (Operating): 0°C to 50°C, <70% R.H.

(Storage): -20°C to 60°C, 0 to 80% R.H., batteries removed

Altitude: up to 2000m

Pollution degree: 2

Safety

Conforms to: BS EN 61010-1 50V

Class II, double insulation

EMC

Conforms to BS EN 61326-1

Related products

THERMOKIT Thermometry Kit

DT173 Single Input K Type Digital Thermometer

Imperial Way, Watford WD24 4PP.

T: +44 (0)1923 44 17 17

www.martindale-electric.co.uk

sales@martindale-electric.co.uk

Ver. G1.0

Due to policy of continuous development, Martindale Electric reserves the right to alter equipment specification and description outlined in this document without prior notice. No part of this document shall be deemed to be part of any contract for the equipment unless specifically referred to as an inclusion within such contract. © 2026 Martindale Electric Co. Ltd.